



PULEGGE SPA 1 gola


Pulley SPA 1 socket




Tipo 1



Tipo 4



Tipo 7



Tipo 9

Pulegge SPA a 1 gola

Descrizione prodotto	Diam. primitivo Dp	Misura bussola	Foro max (bussola)	Diam. esterno Od	Tipo	E	F	J	K	L	M	N	kg
01SPA063	63	1108	28	68.5	9	-	40	36	18	22	-	-	0.65
01SPA067	67	1108	28	72.5	1	-	20	-	-	22	2	62	0.50
01SPA071	71	1108	28	76.5	1	-	20	-	-	22	2	62	0.40
01SPA075	75	1108	28	80.5	1	-	20	-	-	22	2	62	0.50
01SPA080	80	1210	32	85.5	1	-	20	-	-	25	5	75	0.65
01SPA085	85	1210	32	90.5	1	-	20	-	-	25	5	75	0.65
01SPA090	90	1210	32	95.5	1	-	20	-	-	25	5	75	0.60
01SPA095	95	1210	32	100.5	1	-	20	-	-	25	5	75	0.70
01SPA100	100	1610	42	105.5	1	-	20	-	-	25	5	80	0.80
01SPA106	106	1610	42	111.5	1	-	20	-	-	25	5	80	0.90
01SPA112	112	1610	42	117.5	1	-	20	-	-	25	5	80	1.10
01SPA118	118	1610	42	123.5	1	-	20	-	-	25	5	80	1.20
01SPA125	125	1610	42	130.5	1	-	20	-	-	25	5	80	1.30
01SPA132	132	1610	42	137.5	1	-	20	-	-	25	5	80	1.50
01SPA140	140	1610	42	145.5	1	-	20	-	-	25	5	80	1.70
01SPA150	150	1610	42	155.5	7	10	20	-	-	25	5	80	2.00
01SPA160	160	1610	42	165.5	7	8	20	-	-	25	5	80	2.30
01SPA170	170	1610	42	175.5	7	8	20	-	-	25	5	80	2.60
01SPA180	180	1610	42	185.5	7	8	20	150	-	25	5	80	2.50
01SPA190	190	1610	42	195.5	7	8	20	160	-	25	5	80	2.65
01SPA200	200	2012	50	205.5	7	8	20	165	-	32	12	100	2.90
01SPA212	212	2012	50	217.5	7	8	20	176	-	32	12	100	3.10
01SPA224	224	2012	50	229.5	7	8	20	189	-	32	12	100	3.15
01SPA236	236	2012	50	241.5	7	8	20	202	-	32	12	100	3.70
01SPA250	250	2012	50	255.5	4	-	20	215	6	32	6	100	3.60
01SPA280	280	2012	50	285.5	4	-	20	245	-	32	12	100	4.10
01SPA300	300	2012	50	305.5	4	-	20	265	-	32	12	100	5.00
01SPA315	315	2012	50	320.5	4	-	20	280	-	32	12	100	4.60
01SPA355	355	2012	50	360.5	4	-	20	320	-	32	12	100	5.50
01SPA400	400	2012	50	405.5	4	-	20	365	-	32	12	100	6.80
01SPA450	450	2012	50	455.5	4	-	20	415	-	32	12	100	8.40
01SPA500	500	2517	60	505.5	4	-	20	465	-	45	25	120	10.00
01SPA630	630	2517	60	635.5	4	-	20	595	-	45	25	120	17.90

N.B. Il tipo 4 e 5 sono pulegge a raggi.
Le dimensioni non funzionali possono variare.