



PULEGGE SPB 2 gole


Pulley SPB 2 socket




Tipo 1




Tipo 2



Tipo 4



Tipo 7



Tipo 8

Pulegge SPB a 2 gole

Descrizione prodotto	Diam. primitivo Dp	Misura bussola	Foro max (bussola)	Diam. esterno Od	Tipo	E	F	J	K	L	M	N	kg
02SPB100	100	1610	42	107	8	-	44	62	19	25	-	-	1.15
02SPB106	106	1610	42	113	8	-	44	67	19	25	-	-	1.25
02SPB112	112	1610	42	119	2	-	44	72	-	25	19	-	1.7
02SPB118	118	1610	42	125	2	-	44	78	-	25	19	-	1.85
02SPB125	125	2012	50	132	2	-	44	82	-	32	12	-	2
02SPB132	132	2012	50	139	2	-	44	89	-	32	12	-	2.3
02SPB140	140	2012	50	147	2	-	44	97	-	32	12	-	2.8
02SPB150	150	2012	50	157	2	-	44	107	-	32	12	-	3.3
02SPB160	160	2012	50	167	2	-	44	117	-	32	12	-	3.9
02SPB170	170	2012	50	177	2	-	44	127	-	32	12	-	4.5
02SPB180	180	2517	60	187	1	-	44	-	-	45	1	120	5.6
02SPB190	190	2517	60	197	1	-	44	-	-	45	1	120	6.5
02SPB200	200	2517	60	207	1	-	44	-	-	45	1	120	7.5
02SPB212	212	2517	60	219	7	10	44	169	-	45	1	120	6.15
02SPB224	224	2517	60	231	7	10	44	181	1	45	1	120	6.7
02SPB236	236	2517	60	243	7	10	44	193	1	45	1	120	7.15
02SPB250	250	2517	60	257	4	-	44	207	1	45	1	120	7.3
02SPB280	280	2517	60	287	4	-	44	237	1	45	1	120	8.4
02SPB300	300	2517	60	307	4	-	44	257	1	45	1	120	8.75
02SPB315	315	2517	60	322	4	-	44	272	1	45	1	120	9.2
02SPB335	335	2517	60	342	4	-	44	292	1	45	1	120	10.4
02SPB355	355	3020	75	362	4	-	44	312	3.5	51	3.5	150	12.5
02SPB400	400	3020	75	407	4	-	44	357	3.5	51	3.5	150	14.5
02SPB450	450	3020	75	457	4	-	44	407	3.5	51	3.5	150	15.5
02SPB500	500	3020	75	507	4	-	44	457	3.5	51	3.5	150	17
02SPB560	560	3030	75	567	4	-	44	517	4	76	28	150	26.2
02SPB630	630	3030	75	637	4	-	44	587	4	76	28	150	29.7