



PULEGGE SPB 3 gole


Pulley SPB 3 socket




Tipo 2




Tipo 4



Tipo 5



Tipo 6



Tipo 8

Pulegge SPB a 3 gole

Descrizione prodotto	Diam. primitivo Dp	Misura bussola	Foro max (bussola)	Diam. esterno Od	Tipo	E	F	J	K	L	M	N	kg
03SPB100	100	1610	42	107	8	-	63	57	38	25	-	-	1.6
03SPB106	106	1610	42	113	8	-	63	67	38	25	-	-	1.9
03SPB112	112	1610	42	119	2	-	63	72	-	25	38	-	2.2
03SPB118	118	1610	42	125	2	-	63	78	-	25	38	-	2.25
03SPB125	125	2012	50	132	2	-	63	82	-	32	31	-	2.7
03SPB132	132	2012	50	139	2	-	63	89	-	32	31	-	3.2
03SPB140	140	2012	50	147	2	-	63	97	-	32	31	-	3.6
03SPB150	150	2517	60	157	2	-	63	107	-	45	18	-	4.1
03SPB160	160	2517	60	167	2	-	63	117	-	45	18	-	4.8
03SPB170	170	2517	60	177	2	-	63	127	-	45	18	-	5.75
03SPB180	180	2517	60	187	2	-	63	137	-	45	18	-	6.6
03SPB190	190	2517	60	197	2	-	63	147	-	45	18	-	7.5
03SPB200	200	2517	60	207	2	-	63	157	-	45	18	-	8.6
03SPB212	212	2517	60	219	6	20	63	169	-	45	18	120	7.2
03SPB224	224	2517	60	231	6	20	63	181	-	45	18	120	8.2
03SPB236	236	2517	60	243	6	16	63	193	-	45	18	120	9
03SPB250	250	3020	75	257	6	16	63	207	-	51	12	150	10.25
03SPB280	280	3020	75	287	5	-	63	237	6	51	6	150	11.6
03SPB300	300	3020	75	307	5	-	63	257	6	51	6	150	12.15
03SPB315	315	3020	75	322	5	-	63	272	6	51	6	150	12.4
03SPB335	335	3020	75	342	5	-	63	292	6	51	6	150	13.7
03SPB355	355	3020	75	362	5	-	63	312	6	51	6	150	14.3
03SPB400	400	3535	90	407	4	-	63	357	13	89	13	170	21.15
03SPB450	450	3535	90	457	4	-	63	407	-	89	26	170	24.4
03SPB500	500	3535	90	507	4	-	63	457	-	89	26	170	27.1
03SPB560	560	3535	90	567	4	-	63	517	-	89	26	170	35
03SPB630	630	3535	90	637	4	-	63	587	-	89	26	170	41.5
03SPB710	710	3535	90	717	4	-	63	664	4	89	22	170	48.7
03SPB800	800	3535	90	807	4	-	63	754	4	89	22	170	55.1
03SPB900	900	3535	90	907	4	-	63	854	4	89	22	170	63.8
03SPB1000	1.000	4040	100	1007	4	-	63	954	6	102	33	200	82

N.B. Il tipo 4 e 5 sono pulegge a raggi.
Le dimensioni non funzionali possono variare.