


PULEGGE SPC 3 gole


Pulley SPC 3 socket




Tipo 1



Tipo 3



Tipo 4



Tipo 7

Pulegge SPC a 3 gole

Descrizione prodotto	Diam. primitivo Dp	Misura bussola	Foro max (bussola)	Diam. esterno Od	Tipo	E	F	J	K	L	M	N	kg
03SPC200	200	2517	60	209.6	3	-	85	148	20	45	20	-	9.75
03SPC212	212	3020	75	221.6	3	-	85	160	17	51	17	-	10.5
03SPC224	224	3020	75	233.6	3	-	85	173	17	51	17	-	12.1
03SPC236	236	3020	75	245.6	3	-	85	185	17	51	17	-	13.8
03SPC250	250	3020	75	259.6	3	-	85	198	17	51	17	-	15.8
03SPC265	265	3535	90	274.6	1	-	85	215	-	89	4	170	23.2
03SPC280	280	3535	90	289.6	7	25	85	228	-	89	4	170	27.3
03SPC300	300	3535	90	309.6	7	18	85	247	2	89	2	170	21.3
03SPC315	315	3535	90	324.6	7	18	85	262	2	89	2	170	22.25
03SPC335	335	3535	90	344.6	7	18	85	282	2	89	2	170	24.7
03SPC355	355	3535	90	364.6	7	18	85	304	2	89	2	170	23.55
03SPC375	375	3535	90	384.6	4	-	85	324	2	89	2	170	26
03SPC400	400	3535	90	409.6	4	-	85	344	2	89	2	170	28
03SPC425	425	3535	90	434.6	4	-	85	369	2	89	2	170	35
03SPC450	450	3535	90	459.6	4	-	85	394	2	89	2	170	33.4
03SPC475	475	3535	90	484.6	4	-	85	419	2	89	2	170	35.8
03SPC500	500	3535	90	509.6	4	-	85	444	2	89	2	170	36.4
03SPC530	530	3535	90	539.6	4	-	85	474	2	89	2	170	40
03SPC560	560	3535	90	569.6	4	-	85	504	2	89	2	170	47.7
03SPC630	630	4040	100	639.6	4	-	85	574	8.5	102	8.5	200	54.8
03SPC710	710	4040	100	719.6	4	-	85	654	8.5	102	8.5	200	70
03SPC800	800	4545	110	809.6	4	-	85	737	4	114	25	225	81.6
03SPC1000	1.000	5050	125	1009.6	4	-	85	937	8	127	34	245	110.00
03SPC1250	1250	5050	125	1259.6	4	-	85	1187	8	127	34	245	164.8

N.B. Il tipo 4 e 5 sono pulegge a raggi.
Le dimensioni non funzionali possono variare.