



PULEGGE SPC 8 gole


Pulley SPC 8 socket



Tipo 3



Tipo 5



Tipo 6

Pulegge SPC a 8 gole

Descrizione prodotto	Diam. primitivo Dp	Misura bussola	Foro max (bussola)	Diam. esterno Od	Tipo	E	F	J	K	L	M	N	kg
08SPC200	200	3535	90	209.6	3	-	212.5	148	61.75	89	61.75	-	17.9
08SPC212	212	3535	90	221.6	3	-	212.5	160	61.75	89	61.75	-	21
08SPC224	224	3535	90	233.6	3	-	212.5	170	61.75	89	61.75	-	24.2
08SPC236	236	3535	90	245.6	3	-	212.5	184	61.75	89	61.75	-	27
08SPC250	250	3535	90	259.6	3	-	212.5	198	61.75	89	61.75	-	29.1
08SPC265	265	3535	90	274.6	3	-	212.5	213	61.75	89	61.75	-	32.8
08SPC280	280	3535	90	289.6	3	-	212.5	228	61.75	89	61.75	-	40.1
08SPC300	300	4040	100	309.6	3	-	212.5	247	55.25	102	55.25	-	47.8
08SPC315	315	4040	100	324.6	3	-	212.5	258	55.25	102	55.25	-	53.9
08SPC335	335	4040	100	344.6	6	62	212.5	282	55.25	102	55.25	200	44.2
08SPC355	355	4040	100	364.6	3	-	212.5	304	55.25	102	55.25	-	48.1
08SPC375	375	4545	110	384.6	6	20	212.5	324	49.25	114	49.25	225	52.9
08SPC400	400	4545	110	409.6	6	20	212.5	348	49.25	114	49.25	225	61.4
08SPC425	425	4545	125	434.6	6	30	212.5	369	42.75	127	42.75	245	72.7
08SPC450	450	5050	125	459.6	6	30	212.5	394	42.75	127	42.75	245	71.5
08SPC475	475	5050	125	484.6	6	30	212.5	419	42.75	127	42.75	245	89
08SPC500	500	5050	125	509.6	6	30	212.5	444	42.75	127	42.75	245	92.4
08SPC530	530	5050	125	539.6	6	30	212.5	474	42.75	127	42.75	245	94.5
08SPC560	560	5050	125	569.6	5	-	212.5	504	42.75	127	42.75	245	102
08SPC630	630	5050	125	639.6	5	-	212.5	574	42.75	127	42.75	245	105
08SPC710	710	5050	125	719.6	5	-	212.5	656	42.75	127	42.75	245	132
08SPC800	800	5050	125	809.6	5	-	212.5	737	42.75	127	42.75	245	178.5
08SPC1000	1.000	5050	125	1009.6	5	-	212.5	937	42.75	127	42.75	245	236
08SPC1250	1250	5050	125	1259.6	5	-	212.5	1187	42.75	127	42.75	245	267.3

N.B. Il tipo 4 e 5 sono pulegge a raggi.
Le dimensioni non funzionali possono variare.