



PULEGGE SPZ 3 gole

Pulley SPZ 3 socket


Pulegge SPZ a 3 gole




Tipo 2




Tipo 4



Tipo 5



Tipo 6



Tipo 8

Descrizione prodotto	Diam. primitivo Dp	Misura bussola	Foro max (bussola)	Diam. esterno Od	Tipo	E	F	J	K	L	M	N	kg
03SPZ063	63	1108	28	67	8	-	40	40	18	22	-	-	0.5
03SPZ067	67	1108	28	71	8	-	40	42	18	22	-	-	0.5
03SPZ071	71	1108	28	75	8	-	40	42	18	22	-	-	0.7
03SPZ075	75	1210	32	79	8	-	40	48	15	25	-	-	0.6
03SPZ080	80	1210	32	84	8	-	40	51	15	25	-	-	0.7
03SPZ085	85	1610	42	89	8	-	40	60	15	25	-	-	0.75
03SPZ090	90	1610	42	94	8	-	40	61	15	25	-	-	0.9
03SPZ095	95	1610	42	99	8	-	40	66	15	25	-	-	1
03SPZ100	100	1610	42	104	8	-	40	71	15	25	-	-	1.45
03SPZ106	106	1610	42	110	8	-	40	78	15	25	-	-	1.3
03SPZ112	112	2012	50	116	8	-	40	84	8	32	-	-	1.7
03SPZ118	118	2012	50	122	8	-	40	92	8	32	-	-	1.75
03SPZ125	125	2012	50	129	2	-	40	97	-	32	8	-	2
03SPZ132	132	2012	50	136	2	-	40	104	-	32	8	-	2.3
03SPZ140	140	2012	50	144	2	-	40	112	-	32	8	-	2.7
03SPZ150	150	2012	50	154	2	-	40	122	-	32	8	-	3.3
03SPZ160	160	2012	50	164	2	-	40	132	-	32	8	-	3.9
03SPZ170	170	2012	50	174	2	-	40	141	-	32	8	-	4.5
03SPZ180	180	2012	50	184	6	8	40	152	-	32	8	-	3.35
03SPZ190	190	2012	50	194	6	10	40	161	4	32	4	100	3.9
03SPZ200	200	2012	50	204	6	10	40	172	4	32	4	100	3.75
03SPZ224	224	2012	50	228	5	-	40	196	4	32	4	100	5.7
03SPZ250	250	2012	50	254	5	-	40	222	4	32	4	100	4.8
03SPZ280	280	2517	60	284	4	-	40	252	2.5	45	2.5	120	6.4
03SPZ315	315	2517	60	319	4	-	40	287	2.5	45	2.5	120	7
03SPZ355	355	2517	60	359	4	-	40	326	2.5	45	2.5	120	10
03SPZ400	400	2517	60	404	4	-	40	371	2.5	45	2.5	120	10.9
03SPZ450	450	2517	60	454	4	-	40	421	2.5	45	2.5	120	13.4
03SPZ500	500	2517	60	504	4	-	40	471	2.5	45	2.5	120	12.6

N.B. Il tipo 4 e 5 sono pulegge a raggi.
Le dimensioni non funzionali possono variare.