



PULEGGE SPZ 6 gole

Pulley SPZ 6 socket


Pulegge SPZ a 6 gole




Tipo 2




Tipo 4



Tipo 5



Tipo 6



Tipo 8

Descrizione prodotto	Diam. primitivo Dp	Misura bussola	Foro max (bussola)	Diam. esterno Od	Tipo	E	F	J	K	L	M	N	kg
06SPZ090	90	1610	42	94	8	-	76	61	51	25	-	-	1.8
06SPZ095	95	1610	42	99	8	-	76	66	51	25	-	-	2.1
06SPZ100	100	2012	50	104	8	-	76	72	44	32	-	-	2.7
06SPZ106	106	2012	50	110	8	-	76	78	44	32	-	-	2.9
06SPZ112	112	2012	50	116	8	-	76	84	44	32	-	-	2.9
06SPZ118	118	2517	60	122	8	-	76	90	31	45	-	-	3.4
06SPZ125	125	2517	60	129	8	-	76	97	31	45	-	-	3.5
06SPZ132	132	2517	60	136	8	-	76	104	31	45	-	-	3.8
06SPZ140	140	2517	60	144	2	-	76	112	-	45	31	-	4
06SPZ150	150	2517	60	154	2	-	76	122	-	45	31	-	4.6
06SPZ160	160	2517	60	164	2	-	76	132	-	45	31	-	5.8
06SPZ170	170	2517	60	174	2	-	76	141	-	45	31	-	6.4
06SPZ180	180	2517	60	184	2	-	76	152	-	45	31	-	7.2
06SPZ190	190	2517	60	194	6	15	76	161	15	45	15.5	120	6.8
06SPZ200	200	2517	60	204	6	15	76	172	15	45	15.5	120	7.6
06SPZ224	224	2517	60	228	6	15	76	196	15.5	45	15.5	120	9.2
06SPZ250	250	2517	60	254	5	-	76	222	15.5	45	15.5	120	12.2
06SPZ280	280	2517	60	284	5	-	76	252	15.5	45	15.5	120	11.6
06SPZ315	315	2517	60	319	5	-	76	287	15.5	45	15.5	120	15.5
06SPZ355	355	2517	60	359	5	-	76	326	15.5	45	15.5	125	16.5
06SPZ400	400	3030	75	404	5	-	76	371	6.5	76	6.5	150	21.2
06SPZ450	450	3030	75	454	5	-	76	421	6.5	76	6.5	150	19.2