

PULEGGE DENTATE L 050

Pulley L 050




CHAINS ITALY


L 050

PASSO 3/8" (9,525 mm)


PER CINGHIE LARGHEZZA 1/2" (12,7 mm)




10F



11F



13



14

Materiale: Acciaio (St)
Materiale: Ghisa (GG)

tipo	materiale	denti	bussola	foro max	dp	de	Df	Dm	Di	F	L	R	n° flangia	Kg.
10F	St	18	1108	28	54,57	53,81	60	44		19,0	22,0	3	308	0,20
10F	St	19	1108	28	57,61	56,84	63	44		19,0	22,0	3	309	0,23
10F	St	20	1108	28	60,64	59,88	66	48		19,0	22,0	3	310	0,27
10F	St	21	1108	28	63,67	62,91	71	48		19,0	22,0	3	311	0,30
10F	St	22	1108	28	66,70	65,94	75	51		19,0	22,0	3	312	0,34
10F	St	23	1108	28	69,73	68,97	79	54		19,0	22,0	3	313	0,40
10F	St	24	1108	28	72,77	72,00	79	54		19,0	22,0	3	313	0,45
10F	St	25	1108	28	75,80	75,04	83	56		19,0	22,0	3	314	0,50
10F	St	26	1108	28	78,83	78,07	87	60		19,0	22,0	3	315	0,55
10F	St	27	1108	28	81,86	81,10	87	62		19,0	22,0	3	315	0,60
10F	St	28	1108	28	84,89	84,13	91	65		19,0	22,0	3	316	0,65
10F	St	30	1108	28	90,96	90,20	97	70		19,0	22,0	3	318	0,80
10F	St	32	1108	28	97,02	96,26	103	74		19,0	22,0	3	320	0,98
10F	St	36	1108	28	109,15	108,39	115	85		19,0	22,0	3	323	1,20
10F	St	40	1610	42	121,28	120,51	127	97		19,0	25,0	6	327	1,40
11F	St	48	1610	42	145,53	144,77	152	88	120	19,0	25,0	6	334	2,30
13	St	60	1610	42	181,91	181,15		92	166	19,0	25,0	3		2,20
14	GG	72	1610	42	218,30	217,53		92	202	19,0	25,0	3		2,10
14	GG	84	1610	42	254,68	253,90		92	236	19,0	25,0	3		2,46
14	GG	96	2012	50	291,06	290,30		106	270	19,0	32,0	6,5		3,36
14	GG	120	2012	50	363,83	363,07		106	343	19,0	32,0	6,5		4,44